



PICKING UP WHERE OTHERS LEAVE OFF

# ELECTRIC PALLET JACK

## EPT15

**CAPACITY** 3,000 lbs.  
**INTEGRAL BATTERY/CHARGER** (2) 12V 85AH maintenance free batteries with 110VAC 15A plug-in automatic charger



### SPEED

24-volt Curtis travel controller with infinitely variable speed control.

Variable from 0 mph to 2.8 mph empty  
 Variable from 0 mph to 2.5 mph loaded

### WEIGHT

450 lbs. with battery and charger (27x45 Standard)

### TIRES/WHEELS

#### DRIVE

8.3" x 2.8" polyurethane

#### LOAD

(2) 2.9" x 3.5" polyurethane

### TILLER ARM CONTROL

Travel, lift, and lower functions are located in the ergonomic operator handle. All operator controls are accessible without having to lift the hand from the handle. Angle grips are designed to allow easy operation with either hand. Wrap around guard, reversing switch, thumb control, and horn are standard. Low mounted tiller arm offers excellent operator comfort and minimum steering effort.

### ELECTRICAL

Electric braking, quick disconnect EPD power cut off and battery discharge indicator are standard equipment.

### HYDRAULICS

Permanent magnet pump motor and chrome plated lift cylinder provide smooth lifting & lowering. Pump includes DC motor, solenoid, and gear pump.

### BRAKES

Electromagnetic disc brakes.

### DRIVE

24-Volt brushless DC drive motor efficiently delivers up to **6 hours of continuous duty cycle on a single charge.**

### SERVICEABILITY

Removable one piece power head cover allows for easy maintenance.

### AVAILABLE FORK SIZES

27x45 (standard)	• 27x36	• 27x48	• 22x42
	• 27x42	• 22x36	• 22x48

### OPTIONAL EQUIPMENT

- Load back rest, 48" or 60" high
- Tool tray with load restraint
- Traction polyurethane drive tires

### STANDARD TRUCK DIMENSIONS

